

View Online at <https://aerobasegroup.com/nsn/2920-00-675-1302>

Thread Direction:

Right-hand

Thread Length:

0.656 inches

Pilot Diameter:

3.248 inches

Second Step Diameter:

Between 0.749 inches and 0.750 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.312 inches

Mounting Style:

Flange mtd w/three mtg holes

Center To Center Distance Between Mounting Holes Along Width:

3.625 inches

Pilot Height:

0.703 inches

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Counterclockwise

Distance From End To Keyway Center:

1.281 inches

Thread Diameter:

0.500 inches

Maximum Output Current Rating In Amps:

20.0

Rectifier Location:

Separate

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.062 inches

Top Mounting Hole Diameter:

0.625 inches

Bottom Mounting Hole Diameter:

0.468 inches

Center To Center Distance Between Top Mounting Slot And Bottom Mounting Hole:

5.875 inches

Maximum Rated Armature Speed In Rpm:

1300

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

6.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700