

View Online at <https://aerobasegroup.com/nsn/2920-00-695-0539>

Thread Direction:

Right-hand

Thread Length:

0.720 inches

Furnished Items:

Woodruff key

Second Step Diameter:

0.8736 mils and 0.8741 centimeters

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.320 inches

Mounting Style:

No mounting provisions

Environmental Protection:

Corrosion resistant and fungus resistant

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Counterclockwise

Distance From End To Keyway Center:

1.330 inches

Thread Diameter:

0.500 inches

Ground Polarity Type:

Negative or positive

Armature Minimum Speed In Rpm At Full Current Output:

1375

Maximum Output Current Rating In Amps:

20.0

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

12.0

Special Features:

Shaft also projects opposite drive end

Fsc Application Data:

Engine electrical system, nonaircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700