

View Online at <https://aerobasegroup.com/nsn/2920-00-695-7138>

**Mounting Hole Diameter:**

0.281 inches

**Mounting Slot Width:**

0.260 inches

**Mounting Slot Length:**

0.322 inches

**Submersibility:**

Submersible

**Mounting Facility Spacing:**

Holes 1.750 in. C to c slots 1.750 in. C to c

**Voltage Rating:**

12.0 volts

**Closing Voltage Rating:**

Between 3.0 volts and 6.0 volts

**Opening Voltage Rating:**

1.0 volts

**Pull-in Current:**

Between 20.6 amperes and 23.0 amperes

**Hold-in Current:**

Between 3.0 amperes and 4.0 amperes

**Plunger Stroke Length:**

0.375 inches

**Engaging Linkage:**

Not included

**Accommodated Linkage Unthreaded Hole Diameter:**

0.250 inches

**Contact Manual Closing Provision:**

Not included

**Control Terminal Quantity:**

1

**Control Terminal Type:**

Stud

**Grounded Control Terminal:**

Not included

**Main Terminal Quantity:**

2

**Main Terminal Type:**

Stud

**Control Terminal Quantity Internally Connected To Main Terminal:**

1

**Motor Diameter For Which Rigid Mount Is Designed:**

4.438 inches

**Mounting Facility Type And Quantity:**

2 hole and 2 slot

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T130-h