NSN 2920-00-695-7138

Electrical Engine Starter Relay-solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-695-7138 **Mounting Hole Diameter:** 0.281 inches **Mounting Slot Width:** 0.260 inches **Mounting Slot Length:** 0.322 inches Submersibility: Submersible **Mounting Facility Spacing:** Holes 1.750 in. C to c slots 1.750 in. C to c Voltage Rating: 12.0 volts **Closing Voltage Rating:** Between 3.0 volts and 6.0 volts **Opening Voltage Rating:** 1.0 volts **Pull-in Current:** Between 20.6 amperes and 23.0 amperes **Hold-in Current:** Between 3.0 amperes and 4.0 amperes **Plunger Stroke Length:** 0.375 inches **Engaging Linkage:** Not included **Accommodated Linkage Unthreaded Hole Diameter:** 0.250 inches **Contact Manual Closing Provision:** Not included **Control Terminal Quantity: Control Terminal Type: Grounded Control Terminal:** Not included **Main Terminal Quantity: Main Terminal Type:** Stud **Control Terminal Quantity Internally Connected To Main Terminal:**

Motor Diameter For Which Rigid Mount Is Designed:

4.438 inches

NSN 2920-00-695-7138

Electrical Engine Starter Relay-solenoid - Page 2 of 2



Mounting Facility Type And Quantity
2 hole and 2 slot
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T130-h