NSN 2920-00-706-8169

Engine Accessory Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-706-8169 **Thread Direction:** Right-hand Thread Length: 0.490 inches **Pilot Diameter:** 2.250 inches **Second Step Diameter:** 0.630 inches **Keyway Width:** 0.125 inches **Unthreaded Portion Length:** 0.585 inches **Mounting Hole Thread Direction:** Right-hand **Mounting Style:** Flange mtd w/two mtg holes, top hole threaded **Pilot Height:** 0.400 inches **Keyway Length:** 0.562 inches Submersibility: Nonsubmersible **Shaft Rotation Direction:** Counterclockwise **Distance From End To Keyway Center:** 0.750 inches **Thread Diameter:** 0.625 inches **Ground Polarity Type:** Negative **Maximum Output Current Rating In Amps: Grounding Method:** Internal **Shaft Drive End Style:** Straight shaft end, threaded, w/keyway **Distance Between Shaft Center And Bottom Mounting Hole Center:** 3.437 inches **Distance Between Shaft Center And Top Mounting Hole Center:** 3.327 inches

Angular Deviation Of First Hole From Top Center In Deg:

180.0

NSN 2920-00-706-8169

Engine Accessory Generator - Page 2 of 2



Angular Deviation Of Second Hole From First Hole In Deg:
180.0
Bottom Mounting Hole Diameter:
0.385 inches
Thread Series:
Unf
Thread Class:
2a
Mounting Hole Thread Series Designator:
Unc
Mounting Hole Thread Diameter:
0.312 inches
Mounting Hole Thready Qty Per Inch (tpi):
18
Mounting Hole Thread Class:
2b
Thready Qty Per Inch (tpi):
18
Voltage In Volts:
12.0
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
Δ1//700