

View Online at <https://aerobasegroup.com/nsn/2920-00-715-3871>

Thread Direction:

Right-hand

Err Default:

0.490 inches

Second Step Diameter:

Between 0.668 inches and 0.669 inches

Keyway Width:

0.125 inches

Unthreaded Portion Length:

Between 0.804 inches and 0.813 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Environmental Protection:

Corrosion resistant and fungus resistant

Keyway Length:

0.625 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

0.900 inches

Thread Diameter:

0.500 inches

Ground Polarity Type:

Negative

Maximum Output Current Rating In Amps:

40.0

Rectifier Location:

Integral

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.062 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.060 inches

Angular Deviation Of First Hole From Top Center In Deg:

193.0

Angular Deviation Of Second Hole From First Hole In Deg:

164.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 7.115 inches and 7.139 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 7.885 inches and 8.009 inches

Bottom Mounting Hole Diameter:

Between 0.316 inches and 0.324 inches

Maximum Rated Armature Speed In Rpm:

2450

Thread Series:

Uns

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

6.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700