

View Online at <https://aerobasegroup.com/nsn/2920-00-717-3075>

Thread Direction:

Right-hand

Thread Length:

0.750 inches

Pilot Diameter:

Any acceptable

Furnished Items:

Cooling fan and lockwasher and nut and woodruff key

Second Step Diameter:

0.750 inches

Keyway Width:

0.125 inches

Unthreaded Portion Length:

0.810 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Flange mtd w/two mtg holes, top hole threaded

Pilot Height:

Any acceptable

Keyway Length:

0.625 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise or counterclockwise

Distance From End To Keyway Center:

1.155 inches

Thread Diameter:

0.669 inches

Ground Polarity Type:

Negative

Rectifier Location:

Integral

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.310 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.290 inches

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Bottom Mounting Hole Diameter:

0.320 inches

Thread Series:

Uns

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700