

View Online at <https://aerobasegroup.com/nsn/2920-00-726-9545>

Body Style:

Electrically shielded, partial insulator, gasket seat

Dc Resistance Rating In Ohms:

10000.0

Reach Length:

Between 0.359 inches and 0.391 inches

Usage Design:

Engine other than aircraft

Width Across Flats:

Between 0.802 inches and 0.817 inches

Electrode Style:

Single flat shell ground electrode (see also style 4)

Thread Size And Series/type Designator And Location:

14-1.25mm base err-100

Mean Effective Pressure Rating:

135.0 pounds per square inch

Seat Major Diameter:

Between 0.785 inches and 0.800 inches

Height Above Mounting Surface:

2.875 inches

Top To Terminal Contact Distance:

Between 1.245 inches and 1.295 inches

Top To Shield Thread Distance:

Between 0.095 inches and 0.155 inches

Shield Thread Length:

0.375 inches

Barrel Inside Diameter:

Between 0.505 inches and 0.510 inches

Terminal Sleeve Inside Diameter:

Between 0.301 inches and 0.316 inches

Test Data Document:

81348-ws506 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

B class and 1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A10400