## NSN 2920-00-735-4165

Engine Accessory Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-735-4165

| view Online at https://aerobasegroup.com/nsn/2920-00-735-410 |
|--|
| Spline Major Diameter:                                       |
| Between 0.863 inches and 0.867 inches                        |
| Pilot Diameter:  |
| Between 4.120 inches and 4.122 inches                        |
| Furnished Items:   |
| Terminal shield and quick disconnect mounting band           |
| Spline Quantity:   |
| 16   |
| Mounting Hole Diameter:                                      |
| 0.391 inches   |
| Mounting Hole Quantity:                                      |
| 6  |
| Mounting Hole Circle Radius:                                 |
| Between 4.998 inches and 5.002 inches                        |
| Pilot Height:  |
| 0.156 inches   |
| Environmental Protection:                                    |
| Corrosion resistant and fungus resistant                     |
| Submersibility:  |
| Submersible  |
| Shaft Rotation Direction:                                    |
| Counterclockwise   |
| Spline Length:   |
| 1.625 inches   |
| Ground Polarity Type:  |
| Negative or positive   |
| Armature Minimum Speed In Rpm At Full Current Output:        |
| 1600   |
| Maximum Output Current Rating In Amps:                       |
| 25.0   |
| Grounding Method:  |
| Internal   |
| Shaft Drive End Style:                                       |
| Splined shaft end  |
| Angular Deviation Of First Hole From Top Center In Deg:      |
| 39.0   |
| Maximum Rated Armature Speed In Rpm:                         |
| 8000   |
| Voltage In Volts:  |
| 24.0   |

**Fsc Application Data:** 

Engine electrical system, nonaircraft

## NSN 2920-00-735-4165

Engine Accessory Generator - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A14700