

View Online at <https://aerobasegroup.com/nsn/2920-00-735-4460>

**Thread Length:**

0.440 inches

**Second Step Diameter:**

Between 0.668 inches and 0.669 inches

**Keyway Width:**

0.125 inches

**Unthreaded Portion Length:**

0.840 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Environmental Protection:**

Corrosion resistant and fungus resistant

**Keyway Length:**

0.625 inches

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Clockwise

**Maximum Output Current Rating In Amps:**

20.0

**Rectifier Location:**

Separate

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.062 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

3.062 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

196.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

164.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

6.127 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

6.947 inches

**Bottom Mounting Hole Diameter:**

0.320 inches

**Maximum Rated Armature Speed In Rpm:**

2300

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.312 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

18

**Mounting Hole Thread Class:**

2b

**Voltage In Volts:**

12.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700