Ignition Distribution Cap - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-738-1250

| | lication Design: |
|------|--|
| | neto |
| Wid | |
| | 25 inches |
| Len | gth: |
| 3.25 | 50 inches |
| | unting Hole Diameter: |
| 0.18 | 38 inches |
| Μοι | unting Hole Quantity: |
| 4 | |
| Cor | struction Type: |
| One | -piece |
| Fun | gus Resistant Treatment: |
| Not | included |
| Rad | lio Interference Shielding: |
| Not | provided |
| Igni | tion System Design: |
| Sing | |
| Spa | rk Plug Lead Connection Type: |
| Pus | h-in |
| Elec | ctrode Design: |
| Sing | yle |
| Spa | rk Plug Lead Accommodation Quantity: |
| 4 | |
| Spa | rk Plug Lead Accommodation Position: |
| Vert | |
| Exte | ernal Coil Lead Accommodation Quantity: |
| 1 | |
| | Lead Accommodation Position: |
| | zontal |
| | rnal Coil Electrode Type: |
| Rod | |
| - | ing Loaded Brush Type Electrode Accommodation: |
| | uded |
| | rer Accommodation: |
| | |
| | unting Method: |
| Flar | |
| Hei | |
| | 50 inches |
| | If Life: |
| N/a | |

NSN 2920-00-738-1250

Ignition Distribution Cap - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

T130-a

