

View Online at <https://aerobasegroup.com/nsn/2920-00-740-2753>

**Body Material:**

Steel

**Drive Connection Type:**

Coupling half

**Mounting Hole Diameter:**

Between 2.988 inches and 3.000 inches

**Environmental Protection:**

Fungus resistant and submersible

**Performance Type:**

High tension

**Shaft Rotation Direction:**

Clockwise

**Mounting Facility Quantity:**

1

**Pole Quantity:**

2

**Distributor Cap:**

Included

**Mounting Method:**

Base

**Impulse Quantity Per Revolution:**

1

**Ignition Type For Which Designed:**

Single

**Secondary Terminal Type:**

Threaded

**Spark Plug Terminal Accommodation Thread Series:**

Unef

**Coil Terminal Type:**

Threaded

**Coil Terminal Accommodation Thread Series:**

Unef

**Coil Terminal Accommodation Thread Diameter:**

0.750 inches

**Spark Advance Control Method:**

Manual

**Maximum Advance Deg:**

15.0

**Rotation Element Type:**

Permanent magnet rotor

**Contact Set Quantity:**

1

**Mounting Facility:**

Hole

**Features Provided:**

Radio interference shielding

**Spark Distribution Method:**

Gap

**Spark Plug Terminal Accommodation Thread Diameter:**

0.625 inches

**Spark Plug Terminal Accommodation Thready Qty Per Inch (tpi):**

24

**Coil Terminal Accommodation Thready Qty Per Inch (tpi):**

20

**Surface Treatment:**

Enamel

**Surface Treatment:**

Enamel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A12200