

View Online at <https://aerobasegroup.com/nsn/2920-00-753-0817>

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Second Step Diameter:

Between 0.668 inches and 0.669 inches

Keyway Width:

0.125 inches

Unthreaded Portion Length:

0.800 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Keyway Length:

0.625 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

0.900 inches

Thread Diameter:

Between 0.379 inches and 0.387 inches

Maximum Output Current Rating In Amps:

17.0

Rectifier Location:

Separate

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.500 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.500 inches

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Distance Between Inside Surfaces Of Hinge Bracket:

7.127 inches

Distance Between Outside Surfaces Of Hinge Bracket:

8.249 inches

Bottom Mounting Hole Diameter:

Between 0.379 inches and 0.380 inches

Maximum Rated Armature Speed In Rpm:

1450

Thread Series:

Uns

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700