## NSN 2920-00-763-2316

Electrical Engine Starter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-763-2316

| Mounting Hole    | Diameter:   |
|------------------|---|
| Between 0.654 ir | nches and 0.664 inches  |
| Mounting Hole    | Circle Radius:  |
| 2.875 inches     |   |
| Mounting Flang   | e Shape Style:  |
| Triangular       |   |
| Engaging Mech    | anism Style:  |
| Peripheral outbo | ard gear drive w/worm shaft, shaft, shift lever, collar and over-running clutch w/drive housing |
| Engaging Mech    | anism Opening Angular Deviation In Deg:   |
| 77.5             |   |
| Lever Actuation  | n Method:   |
| Solenoid         |   |
| Lock Test Curre  | ent Rating In Amps:   |
| 600.0            |   |
| Shaft Rotation I | Direction:  |
| Clockwise        |   |
| Armature Actua   | tion Device Type:   |
| Relay-solenoid   |   |
| Engaging Mech    | anism To Armature Positional Relationship:  |
| Straight         |   |
| Mounting Flang   | e Angular Deviation In Deg:   |
| 292.5            |   |
| Voltage In Volts | ::  |
| 12.0             |   |
| Terminal Type    | And Quantity:   |
| 2 screw and 1 th | readed stud   |
| Shelf Life:      |   |
| N/a              |   |
| Unit Of Measure  | 2:  |
|                  |   |
| Demilitarization | :   |
| No               |   |
| Fiig:            |   |
| A23400           |   |