Ignition System Distributor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-764-7485

Body Material: Auminum Dive Connection Type: Helical gaar Shaf Longht: Belween 1.742 inches and 1.762 inches Dive Shaft Type: Tongue Shaft Rotation Direction: Counterclockwisa Distributor Cap: Included Mounting Method: Counterclockwisa Distributor Cap: Included Mounting Method: Counterclockwisa Distributor Cap: Included Mounting Method: Counterclockwisa Distributor Cap: Included Mounting Method: Commer Server Mitch Designed: Single Secondary Terminal Type: Pushin Primary Terminal Accommodation Type: Pushin Pushin Pushin Pushin Pushin	
Prive Connection Type:Helical gearShaft Length:Between 1.742 inches and 1.762 inchesDrive Shaft Type:TonguéShaft Rotation Direction:CounterclockwiseDistributor Cap:IncludedMounting Method:ClampInguiseSecondary Terminal Type:PushinPushinPushinPushinPushinVarier Maximum Advance Deg:1010Secondary Terminal Accommodation Type:PushinPushinPushinPushinPushinSecondary Terminal Accommodation Type:PushinSecondary Terminal Accommodation Type:Secondary Terminal Accommodation Type:PushinSecondary Terminal Accommodation Type:Secondary Terminal Ac	Body Material:
Helical gear         Shaft Length:         Between 1.742 inches and 1.762 inches         Drive Shaft Type:         Tongue         Shaft Kotation Direction:         Counterdockwise         Distributor Gap:         Included         Mounting Method:         Clamp         Included         Mounting Method:         Clamp         Included         Mounting Method:         Clamp         Inglies Quantity Per Revolution:         6         Secondary Terminal Type:         Push-In         Push-In         Push-In         Vire lead         Maximum Advance Control Method:         Control Type:         Push-In	
Shift Length:         Between 1.742 inches and 1.762 inches         Drive Shift Type:         Tangua         Tangua         Shaft Action Direction:         Counterclockwise         Distributor Cap:         Included         Mounting Method:         Clamp         Ingules Quantity Per Revolution:         G         Ingules Quantity Per Revolution:         Gingle         State Action Prevention:         Gingle         Path-In         Vianina Type:         Push-In         Push-In         Vianina Accommodation Type:         Wine laad         Spark Advance Control Method:         Caput         Yiani         Guantity         Contertional Method:         Spark Distribution Method:         Spark Distribution Method:         Guantity         Inditity Spark Distribution Method:         Spark Distribution Method:         Spark Distribution Method: <th>Drive Connection Type:</th>	Drive Connection Type:
Between 1.742 inches and 1.762 inchess Drive Shaft Type: Tongue Shaft Rotation Direction: Counterclockwise C	Helical gear
Drive Shaft Type:         Tongue         Shaft Rotation Direction:         Counterclockwise         Distributor Cap:         Included         Mounting Method:         Collar Direction:         Collar Direction:         Included         Mounting Method:         Collar Direction:         Collar Direction:         Sigle         Statistic Type:         Pathian         Social Torminal Type:         Path-In         Post-Intervention:         Coll Terminal Accommodation Type:         Park Advance Control Method:         Contrifugal         Maximum Advance Deg:         12.0         Contact Set Quantity:         12.0         Stat Maximum Advance:         200.0         Stat Maximum Advance:         200.0         Stat Maximum Advance:         Conterve:         Na         Natistic Test Control Method:         Control Method:         Control Method:         Control Method:         Control Control Method:         Control Control Method:         Control Control Method: <t< td=""><th>Shaft Length:</th></t<>	Shaft Length:
Torque         Shaft Rotation Direction:         Conterclockwise         Distributor Cap:         Included         Mounting Method:         Clamp         Implies Quantity Per Revolution:         6         Single         Store of Which Designed:         Single         Store of Which Designed:         Single         Push-in         Pointer Torminal Type:         Push-in         Primary Torminal Accommodation Type:         Wire lead         Spark Advance Control Method:         Contact Set Quantity:         1         Ron At Maximum Advance:         2000         Spark Institution Method:         Contact Set Quantity:         1         Ron At Maximum Advance:         2000         Spark Institution Method:         Contact Set Quantity:         1         Na         Spark Institution Method:         Contact Set Quantity:         1         Rotat Maximum Advance:         2000         Spark Institution Method:         Contact Set Quantity:         Na <t< td=""><th>Between 1.742 inches and 1.762 inches</th></t<>	Between 1.742 inches and 1.762 inches
Shaft Rotation Direction:         Counterclookwise         Distributo Cap:         Included         Mounting Method:         Colamp         Impulse Quantity Per Revolution:         6         Ignite         Store of the Method Designed:         Single         Scondary Terminal Type:         Push-in         Pointinal Type:         Push-in         Vire lead         Spark Advance Control Method:         Conter Set Quantity:         10         Contact Set Quantity:         12         Spark Advance Dag:         12.0         Contact Set Quantity:         12         Contact Set Quantity:         13         Contact Set Quantity:         14         Raminum Advance:         20:0         Spark Distribution Method:         Contact Set Quantity:         12         Contact Set Quantity:         13         Contact Set Quantity:         14         Contact Set Quantity:         15         Contact Set Quantity:         16 <t< td=""><th>Drive Shaft Type:</th></t<>	Drive Shaft Type:
Conterclockwise         Distributor Cap:         Included         Mouning Method:         Clamp         Impulse Quantity Per Revolution:         6         Inglion Type For Which Designed:         Single         Secondary Terminal Type:         Push-in         Coll Terminal Type:         Push-in         Vire lead         Spark Advance Control Method:         Control Xet Quantity:         10         Contact Set Quantity:         12.0         Spark Advance Deg:         12.0         Spark Distribution Method:         20.0         Spark Distribution Method:         20.0         Spark Distribution Method:         Cap         Nai         Na	Tongue
Distributor Cap:IncludedMounting Method:ClampImpulse Quantity Per Revolution:6InglieInglieSecondary Terminal Type:Push-inCoil Terminal Type:Push-inPush-inSecondary Terminal Accommodation Type:Wire leadSerk Advance Control Method:CentrifugalMaximum Advance Deg:11Remark Maximum Advance:200.0Spark Distribution Method:200.0Spark Idstrimum Advance:200.0Spark Idstrimum Advance:201.0202.0203.0203.0203.0203.0	Shaft Rotation Direction:
Included Mounting Method: Gamp Gampa	Counterclockwise
Nounting Method:ClampImpuise Quantity Per Revolution:6Ignition Type For Which Designed:SingleSondary Terminal Type:Push-inColl Terminal Type:Push-inPu	Distributor Cap:
Clanp  Clanp  Clanp  Clanp  Clanp  Clanp  Clantion Type Revolution:  Clantion Type For Which Designed:  Single  Socodary Terminal Type:  Push-in  Coll Terminal Type:  Push-in  Push-in  Push-in  Clantifuigal  Avance Control Method:  Clantifuigal  Avance Deg:  Clantifuigal  Contact Set Quantity:  Clantifuigal	Included
hpulse Quantity Per Revolution:         6         Ignition Type For Which Designed:         Single         Secondary Terminal Type:         Push-in         Poin-inal Accommodation Type:         Wire lead         Spark Advance Control Method:         Centrifugal         Maximum Advance Deg:         12.0         Contact Set Quantity:         1         Repr At Maximum Advance:         220.0         Spark Advance Control Method:         Contact Set Quantity:         1         Repr At Maximum Advance:         220.0         Spark Advance Control Method:         Contact Set Quantity:         1         Repr At Maximum Advance:         220.0         Spark Advance Control Method:         Contact Set Quantity:         1         Repr At Maximum Advance:         220.0         Spark Advance Control Method:         Contact Set Quantity:         10         Gap         Spark Idottion Method:         Contact Set Quantity:         Contact Set Quantity:         Contact Set Quantity =         Contact Set Qu	Mounting Method:
6 Ignition Type For Which Designed: Single Secondary Terminal Type: Push-in Push-in Push-in Primary Terminal Accommodation Type: Push-in Primary Terminal Accommodation Type: Push-in Primary Terminal Accommodation Type: Push-in Push-i	Clamp
Ignition Type For Which Designed:         Single         Secondary Terminal Type:         Push-in         Coll Terminal Type:         Push-in         Push-in <t< th=""><th>Impulse Quantity Per Revolution:</th></t<>	Impulse Quantity Per Revolution:
SingleSecondary Terminal Type:Push-inPush-inPush-inPutinal Accommodation Type:Wire leadSpark Advance Control Method:CentrifugalMaximum Advance Deg:12.0Contact Set Quantity:1Rpm At Maximum Advance:200.0Spark Ibitibution Method:GapShelf Life:N/aUnit Of Measure:-Puniliarization:NoFig:	6
Secondary Terminal Type:Push-inColl Terminal Type:Push-inPurinary Terminal Accommodation Type:Wire leadSpark Advance Control Method:CentrifugalMaximum Advance Deg:12.0Contact Set Quantity:1Spark I Maximum Advance:200.0Spark Distribution Method:GapSheff Life:NaUnit Of Measure:	Ignition Type For Which Designed:
Push-inCoil Terminal Type:Push-inPrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:CentrifugalMaximum Advance Deg:12.0Contact Set Quantity:11Rpm At Maximum Advance:200.0Spark Distribution Method:GapShelf Life:N/aUnit Of Measure:	Single
Coil Terminal Type:Push-inPrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:ContrifugalMaximum Advance Deg:12.0Contact Set Quantity:1Park Maximum Advance:200.0Spark Distribution Method:GapShelf Liffe:N/aUnit Of Measure:-Panel Instruction:NaFig:Fig:	Secondary Terminal Type:
Push-inPrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:CentrifugalMaximum Advance Deg:12.0Contact Set Quantity:1Park Maximum Advance:220.0Spark Distribution Method:GapShelf Life:N/aUnit Of Measure:-Penilitarization:NoFig:	Push-in
Primary Terminal Accommodation Type:Wire leadSpark Advance Control Method:CentrifugalMaximum Advance Deg:12.0Contact Set Quantity:11Rpm At Maximum Advance:200.0Spark Distribution Method:GapShelf Life:N/aUnit of Measure:-Penilitarization:NoFig:	Coil Terminal Type:
Wire leadSpark Advance Control Method:CentrifugalMaximum Advance Deg:12.0Contact Set Quantity:11Rpm At Maximum Advance:2200.0Spark Distribution Method:GapShelf Life:N/aUnit of Measure:Demilitarization:NoFig:	Push-in
Spark Advance Control Method:CentrifugalMaximum Advance Deg:12.0Contact Set Quantity:11Rpm At Maximum Advance:2200.0Spark Distribution Method:GapShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	Primary Terminal Accommodation Type:
Centrifugal Maximum Advance Deg: 12.0 Contact Set Quantity: 1 1 Contact Set Quantity: 1 2 Contact Set Quantity: 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Wire lead
Maximum Advance Deg:12.0Contact Set Quantity:11Rpm At Maximum Advance:2200.0Spark Distribution Method:GapShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:	Spark Advance Control Method:
12.0 Contact Set Quantity: 1 Rpm At Maximum Advance: 2200.0 Spark Distribution Method: Gap Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Centrifugal
Contact Set Quantity:11Rpm At Maximum Advance:2200.0Spark Distribution Method:GapShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	Maximum Advance Deg:
1         Rpm At Maximum Advance:         2200.0         Spark Distribution Method:         Gap         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	12.0
Rpm At Maximum Advance:         2200.0         Spark Distribution Method:         Gap         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Contact Set Quantity:
2200.0 Spark Distribution Method: Gap Shelf Life: N/a Unit Of Measure: Demilitarization: No	1
Spark Distribution Method:         Gap         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Rpm At Maximum Advance:
Gap Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	2200.0
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Spark Distribution Method:
N/a Unit Of Measure:  Demilitarization: No	Gap
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
	Fiig: