

View Online at <https://aerobasegroup.com/nsn/2920-00-771-3901>

Thread Direction:

Right-hand

Thread Length:

0.578 inches

Furnished Items:

Cooling fan and lockwasher and nut and woodruff key

Second Step Diameter:

0.750 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

0.844 inches

Mounting Style:

Bracket mtd w/three mtg holes

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Thread Diameter:

0.500 inches

Ground Polarity Type:

Negative

Armature Minimum Speed In Rpm At Full Current Output:

825

Maximum Output Current Rating In Amps:

55.0

Grounding Method:

Internal

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

4.438 inches

Distance Between Shaft Center And Top Mounting Hole Center:

4.438 inches

Angular Deviation Of First Hole From Top Center In Deg:

196.0

Angular Deviation Of Second Hole From First Hole In Deg:

118.5

Distance Between Inside Surfaces Of Hinge Bracket:

Between 8.774 inches and 8.787 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 9.774 inches and 9.787 inches

Top Mounting Hole Diameter:

Between 0.089 inches and 0.099 inches

Bottom Mounting Hole Diameter:

Between 0.214 inches and 0.224 inches

Maximum Rated Armature Speed In Rpm:

1080

Thread Class:

2a

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A14700