Engine Accessory Generator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/2920-00-782-4156



Thread Direction:	
Right-hand	
Thread Length:	
0.750 inches	
Second Step Diameter:	
Between 0.7794 inches and 0.780 inches	
Keyway Width:	
0.156 inches	
Unthreaded Portion Length:	
Between 1.220 inches and 1.245 inches	
Mounting Hole Thread Direction:	
Right-hand	
Mounting Style:	
Bracket mtd w/three mtg holes, top hole threaded	
Environmental Protection:	
Corrosion resistant and fungus resistant	
Keyway Length:	
0.750 inches	
Submersibility:	
Submersible	
Maximum Operating Altitude Rating:	
Not rated	
Shaft Rotation Direction:	
Counterclockwise	
Distance From End To Keyway Center:	
1.405 inches	
Thread Diameter:	
0.750 inches	
Ground Polarity Type:	
Negative	
Armature Minimum Speed In Rpm At Full Current Output:	
5000	
Maximum Output Current Rating In Amps:	
80.0	
Minimum Current Cut-in Speed In Rpm:	
1500	
Rectifier Location:	
Integral	
Grounding Method:	
Internal	
Shaft Drive End Style:	
Straight shaft end, threaded, w/keyway	



## Distance Between Shaft Center And Bottom Mounting Hole Center: Between 4.430 inches and 4.440 inches Distance Between Shaft Center And Top Mounting Hole Center: Between 4.430 inches and 4.440 inches Angular Deviation Of First Hole From Top Center In Deg: 0.0 Angular Deviation Of Second Hole From First Hole In Deg: 0.00.0 **Distance Between Inside Surfaces Of Hinge Bracket:** Between 6.631 inches and 6.644 inches **Distance Between Outside Surfaces Of Hinge Bracket:** Between 8.131 inches and 8.144 inches **Bottom Mounting Hole Diameter:** Between 0.627 inches and 0.630 inches Maximum Rated Armature Speed In Rpm: 50000 **Thread Series:** Unf **Thread Class:** 2a Mounting Hole Thread Series Designator: Unf **Mounting Hole Thread Diameter:** 0.625 inches Mounting Hole Thready Qty Per Inch (tpi): 18 Mounting Hole Thread Class: 2b Thready Qty Per Inch (tpi): 16 Voltage In Volts: 28.0 Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A14700