NSN 2920-00-810-7082

Spark Plug - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-810-7082

D			Stv	. 1	
D	ou	IV	SIV	и	е.

Electrically shielded, partial insulator, gasket seat

Dc Resistance Rating In Ohms:

10000.0

Reach Length:

Between 0.484 inches and 0.516 inches

Usage Design:

Engine other than aircraft

Width Across Flats:

Between 0.865 inches and 0.880 inches

Electrode Style:

B1 single flat shell ground electrode (see also style 4)

Thread Size And Series/type Designator And Location:

18-1.5mm base err-100

Mean Effective Pressure Rating:

135.0 pounds per square inch

Seat Major Diameter:

Between 0.865 inches and 0.980 inches

Height Above Mounting Surface:

2.875 inches

Top To Terminal Contact Distance:

Between 1.220 inches and 1.320 inches

Top To Shield Thread Distance:

Between 0.094 inches and 0.156 inches

Shield Thread Length:

0.375 inches

Barrel Inside Diameter:

Between 0.505 inches and 0.510 inches

Terminal Sleeve Inside Diameter:

Between 0.301 inches and 0.316 inches

Special Features:

Grumman aerospace corporation a10 aircraft

Specification Or Standard:

1 type and a class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A10400