## NSN 2920-00-810-7082

Spark Plug - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-810-7082

D			Stv	.1	_	
D	ou	IV	ÐΙ	/	е	

Electrically shielded, partial insulator, gasket seat

Dc Resistance Rating In Ohms:

10000.0

Reach Length:

Between 0.484 inches and 0.516 inches

**Usage Design:** 

Engine other than aircraft

Width Across Flats:

Between 0.865 inches and 0.880 inches

**Electrode Style:** 

B1 single flat shell ground electrode (see also style 4)

Thread Size And Series/type Designator And Location:

18-1.5mm base err-100

**Mean Effective Pressure Rating:** 

135.0 pounds per square inch

**Seat Major Diameter:** 

Between 0.865 inches and 0.980 inches

**Height Above Mounting Surface:** 

2.875 inches

**Top To Terminal Contact Distance:** 

Between 1.220 inches and 1.320 inches

**Top To Shield Thread Distance:** 

Between 0.094 inches and 0.156 inches

**Shield Thread Length:** 

0.375 inches

**Barrel Inside Diameter:** 

Between 0.505 inches and 0.510 inches

**Terminal Sleeve Inside Diameter:** 

Between 0.301 inches and 0.316 inches

**Special Features:** 

Grumman aerospace corporation a10 aircraft

**Specification Or Standard:** 

1 type and a class

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A10400