NSN 2920-00-821-2281

Spark Plug - Page 1 of 1



om/nsn/2920-00-821-2281

View Online at https://aerobasegroup.com/nsn/2920-00-82
Body Style:
Electrically shielded, partial insulator, gasket seat
Dc Resistance Rating In Ohms:
Between 2000.0 and 20000.0
Reach Length:
0.750 inches
Usage Design:
Engine other than aircraft
Width Across Flats:
Between 0.802 inches and 0.817 inches
Electrode Style:
B1 single flat shell ground electrode (see also style 4)
Thread Size And Series/type Designator And Location:
14-1.25mm base err-100
Mean Effective Pressure Rating:
275.0 pounds per square inch
Seat Major Diameter:
0.790 inches
Height Above Mounting Surface:
2.500 inches
Top To Terminal Contact Distance:
Between 1.220 inches and 1.320 inches
Top To Shield Thread Distance:
Between 0.095 inches and 0.155 inches
Shield Thread Length:
Between 0.565 inches and 0.675 inches
Barrel Inside Diameter:
Between 0.505 inches and 0.515 inches
Terminal Sleeve Inside Diameter:
Between 0.301 inches and 0.316 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A10400