## NSN 2920-00-848-9151

Electrical Engine Starter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-848-9151

| Mounting Hole Diame    | eter:                                                                                      |
|------------------------|--------------------------------------------------------------------------------------------|
| Between 0.654 inches   | and 0.664 inches                                                                           |
| Mounting Hole Circle   | Radius:                                                                                    |
| 2.875 inches           |                                                                                            |
| Mounting Flange Sha    | ipe Style:                                                                                 |
| Triangular             |                                                                                            |
| Engaging Mechanisn     | n Style:                                                                                   |
| Peripheral outboard ge | ear drive w/worm shaft, shaft, shift lever, collar and over-running clutch w/drive housing |
| Engaging Mechanisn     | n Opening Angular Deviation In Deg:                                                        |
| 282.0                  |                                                                                            |
| Lever Actuation Meth   | nod:                                                                                       |
| Solenoid               |                                                                                            |
| Lock Test Current Ra   | iting In Amps:                                                                             |
| 600.0                  |                                                                                            |
| Shaft Rotation Direct  | ion:                                                                                       |
| Clockwise              |                                                                                            |
| Armature Actuation I   | Device Type:                                                                               |
| Relay-solenoid         |                                                                                            |
| Engaging Mechanisn     | n To Armature Positional Relationship:                                                     |
| Straight               |                                                                                            |
| Mounting Flange Ang    | gular Deviation In Deg:                                                                    |
| 67.0                   |                                                                                            |
| Voltage In Volts:      |                                                                                            |
| 12.0                   |                                                                                            |
| Terminal Type And Q    | luantity:                                                                                  |
| 2 threaded stud        |                                                                                            |
| Shelf Life:            |                                                                                            |
| N/a                    |                                                                                            |
| Unit Of Measure:       |                                                                                            |
|                        |                                                                                            |
| Demilitarization:      |                                                                                            |
| No                     |                                                                                            |
| Fiig:                  |                                                                                            |
| A23400                 |                                                                                            |