

View Online at <https://aerobasegroup.com/nsn/2920-00-867-6580>

**Body Material:**

Aluminum alloy

**Drive Connection Type:**

Impulse coupled

**Mounting Slot Width:**

0.430 inches

**Mounting Slot Length:**

1.125 inches

**Shaft Length:**

0.438 inches

**Distance Between Mounting Facility Centers:**

4.200 inches

**Performance Type:**

High tension

**Drive Shaft Type:**

Threaded

**Shaft Rotation Direction:**

Counterclockwise

**Mounting Facility Quantity:**

1

**Pole Quantity:**

2

**Distributor Cap:**

Included

**Mounting Method:**

Flange

**Impulse Quantity Per Revolution:**

2

**Ignition Type For Which Designed:**

Single

**Secondary Terminal Type:**

Push-in

**Mounting Standard Controlling Agency:**

Sae

**Mounting Standard Number:**

J546

**Spark Advance Control Method:**

Manual

**Maximum Advance Deg:**

20.0

**Rotation Element Type:**

Permanent magnet rotor

**Contact Set Quantity:**

1

**Mounting Facility:**

Slot and threaded hole

**Spark Distribution Method:**

Gap

**Mounting Facility Thread Series:**

Unc

**Mounting Facility Thread Diameter:**

0.375 inches

**Mounting Facility Thready Qty Per Inch (tpi):**

16

**Special Features:**

Black enamel

**Surface Treatment:**

Enamel

**Surface Treatment:**

Enamel, black

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A12200