NSN 2920-00-867-6580



Ignition Magneto - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/2920-00-867-6580 **Body Material:** Aluminum alloy **Drive Connection Type:** Impulse coupled **Mounting Slot Width:** 0.430 inches **Mounting Slot Length:** 1.125 inches **Shaft Length:** 0.438 inches **Distance Between Mounting Facility Centers:** 4.200 inches **Performance Type:** High tension **Drive Shaft Type:** Threaded **Shaft Rotation Direction:** Counterclockwise **Mounting Facility Quantity: Pole Quantity:** 2 **Distributor Cap:** Included **Mounting Method:** Flange Impulse Quantity Per Revolution: **Ignition Type For Which Designed:** Single **Secondary Terminal Type: Mounting Standard Controlling Agency:** Sae **Mounting Standard Number: Spark Advance Control Method:**

J546 Manual **Maximum Advance Deg:** 20.0 **Rotation Element Type:** Permanent magnet rotor

NSN 2920-00-867-6580 Ignition Magneto - Page 2 of 2



| Contact Set Quantity: |
|---|
| 1 |
| Mounting Facility: |
| Slot and threaded hole |
| Spark Distribution Method: |
| Gap |
| Mounting Facility Thread Series: |
| Jnc |
| Mounting Facility Thread Diameter: |
| 0.375 inches |
| Mounting Facility Thready Qty Per Inch (tpi): |
| 16 |
| Special Features: |
| Black enamel |
| Surface Treatment: |
| Enamel |
| Surface Treatment: |
| Enamel, black |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . - |
| Demilitarization: |
| No |
| Fiig: |
| A12200 |