

View Online at <https://aerobasegroup.com/nsn/2920-00-885-3639>

Mounting Slot Width:

Between 0.270 inches and 0.290 inches

Mounting Slot Length:

Between 0.370 inches and 0.390 inches

Submersibility:

Nonsubmersible

Mounting Facility Spacing:

1.740 in. Min 1.760 in. Maximum c to c

Voltage Rating:

24.0 volts

Closing Voltage Rating:

24.0 volts

Pull-in Current:

Between 41.6 amperes and 45.8 amperes

Hold-in Current:

7.3 volt-ampere and 8.3 microwatts

Plunger Stroke Length:

0.750 inches

Engaging Linkage:

Not included

Accommodated Linkage Threaded Hole Thread Size:

3/8-20

Contact Manual Closing Provision:

Not included

Control Terminal Quantity:

1

Control Terminal Type:

Screw

Grounded Control Terminal:

Included

Main Terminal Quantity:

2

Main Terminal Type:

Stud

Control Terminal Quantity Internally Connected To Main Terminal:

1

Motor Diameter For Which Rigid Mount Is Designed:

5.562 inches

Mounting Facility Type And Quantity:

4 slot

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T130-h