

View Online at <https://aerobasegroup.com/nsn/2920-00-890-9886>

Body Material:

Any acceptable

Drive Connection Type:

Impulse coupled

Mounting Slot Width:

Between 0.403 inches and 0.414 inches

Mounting Slot Length:

1.137 inches

Shaft Length:

Between 0.734 inches and 0.750 inches

Distance Between Mounting Facility Centers:

Between 4.182 inches and 4.194 inches

Performance Type:

High tension

Drive Shaft Type:

Keyway shaft

Shaft Rotation Direction:

Clockwise

Mounting Facility Quantity:

1 and 1

Pole Quantity:

2

Distributor Cap:

Included

Mounting Method:

Flange

Impulse Quantity Per Revolution:

2

Ignition Type For Which Designed:

Single

Secondary Terminal Type:

Threaded

Spark Plug Terminal Accommodation Thread Series:

Unef

Mounting Standard Controlling Agency:

Sae

Mounting Standard Number:

J546

Rotation Element Type:

Permanent magnet rotor

Contact Set Quantity:

1

Mounting Facility:

Slot and threaded hole

Features Provided:

Radio interference shielding

Spark Distribution Method:

Gap

Spark Plug Terminal Accommodation Thread Diameter:

0.625 inches

Spark Plug Terminal Accommodation Thread Qty Per Inch (tpi):

24

Mounting Facility Thread Series:

Unc

Mounting Facility Thread Diameter:

0.375 inches

Mounting Facility Thread Qty Per Inch (tpi):

16

Special Features:

Second drive connection type helical gear

Surface Treatment:

Enamel

Surface Treatment:

Enamel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A12200