NSN 2920-00-905-1485

Electrical Engine Starter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-905-1485

| Mounting Hole | Diameter: |
|------------------|--|
| Between 0.654 | inches and 0.664 inches |
| Mounting Hole | Circle Radius: |
| 2.875 inches | |
| Mounting Flan | ge Shape Style: |
| Triangular | |
| Engaging Mecl | hanism Style: |
| Peripheral outbo | bard gear drive w/worm shaft, shaft, shift lever, collar and over-running clutch w/drive housing |
| Engaging Mecl | hanism Opening Angular Deviation In Deg: |
| 142.5 | |
| Lever Actuatio | n Method: |
| Solenoid | |
| Lock Test Curr | ent Rating In Amps: |
| 600.0 | |
| Shaft Rotation | Direction: |
| Counterclockwis | Se |
| Armature Actu | ation Device Type: |
| Relay-solenoid | |
| Engaging Mecl | hanism To Armature Positional Relationship: |
| Straight | |
| Mounting Flan | ge Angular Deviation In Deg: |
| 322.5 | |
| Voltage In Volt | s: |
| 12.0 | |
| Terminal Type | And Quantity: |
| 1 threaded stud | |
| Shelf Life: | |
| N/a | |
| Unit Of Measur | e: |
| | |
| Demilitarizatio | n: |
| No | |
| Fiig: | |
| A23400 | |