

View Online at <https://aerobasegroup.com/nsn/2920-00-913-4532>

**Thread Direction:**

Right-hand

**Thread Length:**

0.814 inches

**Second Step Diameter:**

Between 0.873 inches and 0.874 inches

**Keyway Width:**

0.156 inches

**Unthreaded Portion Length:**

1.320 inches

**Mounting Style:**

Bracket mtd w/two mtg holes

**Environmental Protection:**

Corrosion resistant

**Keyway Length:**

0.750 inches

**Shaft Rotation Direction:**

Clockwise or counterclockwise

**Thread Diameter:**

0.625 inches

**Maximum Output Current Rating In Amps:**

62.0

**Rectifier Location:**

Integral

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.830 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

180.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

3.965 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

5.105 inches

**Bottom Mounting Hole Diameter:**

0.451 inches

**Thread Series:**

Unf

**Thread Class:**

2a

**Thready Qty Per Inch (tpi):**

18

**Voltage In Volts:**

12.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A14700