## NSN 2920-00-914-2204

Engine Accessory Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-914-2204
Thread Direction:
Right-hand
Thread Length:
1.000 inches
Furnished Items:
Bolt and bracket and bushing package and cooling fan and cover plate and dowel and gasket and lead assembly and lockwasher and
mounting band and nut and screw and woodruff key
Second Step Diameter:
0.668 mils and 0.669 centimeters
Keyway Width:
0.125 inches
Unthreaded Portion Length:
0.812 inches
Mounting Hole Thread Direction:
Right-hand
Mounting Style:
Bracket mtd w/three mtg holes, top hole threaded
Keyway Length:
0.625 inches
Submersibility:
Nonsubmersible
Shaft Rotation Direction:
Clockwise
Distance From End To Keyway Center:
1.400 inches
Thread Diameter:
0.625 inches
Ground Polarity Type:
Negative or positive
Armature Minimum Speed In Rpm At Full Current Output:
2950
Maximum Output Current Rating In Amps:
35.0
Grounding Method:
External
Shaft Drive End Style:
Straight shaft end, threaded, w/keyway
Distance Between Shaft Center And Bottom Mounting Hole Center:
Between 3.052 inches and 3.072 inches
Distance Between Shaft Center And Top Mounting Hole Center:
3.060 inches

193.0

Angular Deviation Of First Hole From Top Center In Deg:

## NSN 2920-00-914-2204 Engine Accessory Generator - Page 2 of 2



Angular Deviation Of Second Hole From First Hole In Deg:
164.0
Distance Between Inside Surfaces Of Hinge Bracket:
Between 6.115 inches and 6.139 inches
Distance Between Outside Surfaces Of Hinge Bracket:
Between 7.025 inches and 7.049 inches
Bottom Mounting Hole Diameter:
Between 0.379 inches and 0.387 inches
Thread Series:
Jnf
Thread Class:
2a
Mounting Hole Thread Series Designator:
Jnc
Mounting Hole Thread Diameter:
0.312 inches
Mounting Hole Thready Qty Per Inch (tpi):
18
Mounting Hole Thread Class:
2b
Гhready Qty Per Inch (tpi):
18
Voltage In Volts:
3.0
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A14700