

View Online at <https://aerobasegroup.com/nsn/2920-00-923-2529>

Mounting Hole Diameter:

0.315 mils and 0.335 centimeters

Mounting Slot Width:

Between 0.255 inches and 0.265 inches

Mounting Slot Length:

Between 0.315 inches and 0.355 inches

Submersibility:

Nonsubmersible

Mounting Facility Spacing:

Holes and slots 66 degrees c to c on 2.520 in. Min 2.540 in. Maximum radius

Voltage Rating:

20.0 volts

Closing Voltage Rating:

20.0 volts

Pull-in Current:

Between 35.0 amperes and 39.0 amperes

Hold-in Current:

6.750 microwatts

Engaging Linkage:

Not included

Contact Manual Closing Provision:

Not included

Control Terminal Quantity:

1

Control Terminal Type:

Stud

Grounded Control Terminal:

Not included

Main Terminal Quantity:

2

Main Terminal Type:

Stud

Control Terminal Quantity Internally Connected To Main Terminal:

1

Motor Diameter For Which Rigid Mount Is Designed:

5.062 inches

Mounting Facility Type And Quantity:

2 hole and 2 slot

Surface Treatment:

Zinc

Surface Treatment:

Zinc plated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T130-h