Engine Accessory Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-947-5503

Thread Direction:
Right-hand
Thread Length:
Between 0.460 inches and 0.550 inches
Furnished Items:
Woodruff key
Second Step Diameter:
Between 0.6684 inches and 0.669 inches
Keyway Width:
0.625 inches
Unthreaded Portion Length:
Between 0.750 inches and 0.840 inches
Mounting Hole Thread Direction:
Right-hand
Mounting Style:
Bracket mtd w/three mtg holes, top hole threaded
Keyway Length:
0.625 inches
Submersibility:
Nonsubmersible
Maximum Operating Altitude Rating:
Not rated
Shaft Rotation Direction:
Counterclockwise
Distance From End To Keyway Center:
0.900 inches
Thread Diameter:
0.625 inches
Ground Polarity Type:
Negative or positive
Armature Minimum Speed In Rpm At Full Current Output:
1970
Maximum Output Current Rating In Amps:
25.0
Grounding Method:
External
Shaft Drive End Style:
Straight shaft end, threaded, w/keyway
Distance Between Shaft Center And Bottom Mounting Hole Center:
Between 3.052 inches and 3.072 inches
Distance Between Shaft Center And Top Mounting Hole Center:
3.060 inches



Angular Deviation Of First Hole From Top Center In Deg:
193.0
Angular Deviation Of Second Hole From First Hole In Deg:
164.0
Distance Between Inside Surfaces Of Hinge Bracket:
Between 7.115 inches and 7.139 inches
Distance Between Outside Surfaces Of Hinge Bracket:
Between 7.935 inches and 7.959 inches
Bottom Mounting Hole Diameter:
Between 0.379 inches and 0.387 inches
Maximum Rated Armature Speed In Rpm:
Not rated
Thread Series:
Un
Thread Class:
2a
Mounting Hole Thread Series Designator:
Unc
Mounting Hole Thread Diameter:
0.312 inches
Mounting Hole Thready Qty Per Inch (tpi):
18
Mounting Hole Thread Class:
2b
Thready Qty Per Inch (tpi):
20
Voltage In Volts:
12.0
Fsc Application Data:
Engine electrical system, nonaircraft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A14700