

View Online at <https://aerobasegroup.com/nsn/2920-00-979-3504>

Body Material:

Aluminum alloy

Drive Connection Type:

Rigid coupled

Mounting Slot Width:

0.402 inches

Mounting Slot Length:

1.000 inches

Environmental Protection:

Dustproof

Distance Between Mounting Facility Centers:

4.205 inches

Performance Type:

Low tension

Drive Shaft Type:

Tongue

Shaft Rotation Direction:

Clockwise

Mounting Facility Quantity:

1 and 1

Pole Quantity:

2

Distributor Cap:

Included

Mounting Method:

Flange

Impulse Quantity Per Revolution:

2

Ignition Type For Which Designed:

Single

Secondary Terminal Type:

Threaded

Spark Plug Terminal Accommodation Thread Series:

Unef

Mounting Standard Controlling Agency:

Sae

Mounting Standard Number:

J546

Spark Advance Control Method:

Centrifugal

Maximum Advance Deg:

Any acceptable

Rotation Element Type:

Permanent magnet rotor

Rpm At Maximum Advance:

Any acceptable

Mounting Facility:

Slot and threaded hole

Spark Distribution Method:

Contact

Spark Plug Terminal Accommodation Thread Diameter:

0.625 inches

Spark Plug Terminal Accommodation Thready Qty Per Inch (tpi):

24

Mounting Facility Thread Series:

Unc

Mounting Facility Thread Diameter:

0.375 inches

Mounting Facility Thready Qty Per Inch (tpi):

16

Surface Treatment:

Any acceptable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A12200