

View Online at https://aerobasegroup.com/nsn/2920-00-981-4936

Furnished Items:
Capacitor and cooling fan
Keyway Width:
Between 0.249 inches and 0.250 inches
Unthreaded Portion Length:
1.860 inches
Mounting Hole Thread Direction:
Right-hand
Mounting Style:
Bracket mtd w/three mtg holes, top hole threaded
Environmental Protection:
Corrosion resistant and fungus resistant
Keyway Length:
1.250 inches
Largest Diameter:
Between 0.9990 inches and 0.9995 inches
Submersibility:
Nonsubmersible
Maximum Operating Altitude Rating:
Not rated
Shaft Rotation Direction:
Counterclockwise
Distance From End To Keyway Center:
0.625 inches
Input Current Rating:
500.0 amperes
Maximum Output Current Rating In Amps:
300.0
Shaft Drive End Style:
Straight shaft end w/keyway
Distance Between Shaft Center And Bottom Mounting Hole Center:
Between 4.745 inches and 4.755 inches
Distance Between Shaft Center And Top Mounting Hole Center:
Between 4.745 inches and 4.755 inches
Angular Deviation Of First Hole From Top Center In Deg:
240.0
Angular Deviation Of Second Hole From First Hole In Deg:
120.0
Distance Between Inside Surfaces Of Hinge Bracket:
6.940 inches
Distance Between Outside Surfaces Of Hinge Bracket:
8.840 inches



Bottom Mounting Hole Diameter: Between 0.448 inches and 0.458 inches Mounting Hole Thread Series Designator: Unf Mounting Hole Thread Diameter: 0.438 inches Mounting Hole Thready Qty Per Inch (tpi): 20 Mounting Hole Thread Class: 2b **Product Name:** Starter-generator, engine Voltage In Volts: 30.0 Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A14700