

View Online at <https://aerobasegroup.com/nsn/2920-00-983-4326>

Thread Length:

0.435 inches

Second Step Diameter:

Between 0.668 inches and 0.669 inches

Keyway Width:

0.125 inches

Unthreaded Portion Length:

0.840 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Keyway Length:

0.625 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Maximum Output Current Rating In Amps:

25.0

Rectifier Location:

Separate

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.062 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.062 inches

Angular Deviation Of First Hole From Top Center In Deg:

196.0

Angular Deviation Of Second Hole From First Hole In Deg:

164.0

Distance Between Inside Surfaces Of Hinge Bracket:

7.127 inches

Distance Between Outside Surfaces Of Hinge Bracket:

7.937 inches

Bottom Mounting Hole Diameter:

0.320 inches

Maximum Rated Armature Speed In Rpm:

1970

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700