## NSN 2920-00-985-0273

Electrical Engine Starter Relay-solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-985-0273 **Mounting Hole Diameter:** 0.275 inches Submersibility: Nonsubmersible **Mounting Facility Spacing:** 1.405 in. C to c **Voltage Rating:** 24.0 volts **Closing Voltage Rating:** Between 20.0 volts and 24.0 volts **Pull-in Current:** Between 35.0 amperes and 39.0 amperes **Hold-in Current:** 6.75 amperes **Plunger Stroke Length:** 6.000 inches **Engaging Linkage:** Not included **Err Default:** Err default **Contact Manual Closing Provision:** Not included **Control Terminal Quantity: Control Terminal Type:** Stud **Grounded Control Terminal:** Included **Main Terminal Quantity: Main Terminal Type: Control Terminal Quantity Internally Connected To Main Terminal:** 1 Motor Diameter For Which Rigid Mount Is Designed: Between 5.062 inches and 5.125 inches **Mounting Facility Type And Quantity:** 4 hole Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 2920-00-985-0273

Electrical Engine Starter Relay-solenoid - Page 2 of 2



D	:1:4.	-:-	-4:-	
Dem	HIT	arız	atıc	on:

No

Fiig:

T130-h