

View Online at <https://aerobasegroup.com/nsn/2920-00-987-6231>

Thread Pitch Diameters:

+0.6324/+0.6365 inches

Thread Direction:

Right-hand

Thread Length:

Between 0.460 inches and 0.550 inches

Furnished Items:

Woodruff key

Second Step Diameter:

Between 0.6684 inches and 0.669 inches

Keyway Width:

0.125 inches

Unthreaded Portion Length:

Between 0.750 inches and 0.840 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Keyway Length:

0.625 inches

Submersibility:

Nonsubmersible

Maximum Operating Altitude Rating:

Not rated

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

0.900 inches

Thread Diameter:

0.669 inches

Armature Minimum Speed In Rpm At Full Current Output:

1900

Maximum Output Current Rating In Amps:

18.0

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

Between 3.865 inches and 3.885 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.500 inches

Angular Deviation Of First Hole From Top Center In Deg:

193.0

Angular Deviation Of Second Hole From First Hole In Deg:

159.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 7.118 inches and 7.136 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 7.998 inches and 8.016 inches

Bottom Mounting Hole Diameter:

Between 0.379 inches and 0.387 inches

Maximum Rated Armature Speed In Rpm:

Not rated

Thread Series:

Uns

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

24.0

Fsc Application Data:

Engine electrical system, nonaircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700