NSN 2920-00-989-3335

Electrical Engine Starter Relay-solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-989-3335 **Mounting Slot Width:** Between 0.260 inches and 0.280 inches **Mounting Slot Length:** Between 0.330 inches and 0.350 inches Submersibility: Nonsubmersible **Mounting Facility Spacing:** 3.050 in. To 3.070 in. C Voltage Rating: 24.0 volts **Pull-in Current:** Between 8.7 amperes and 9.2 amperes **Plunger Stroke Length:** 0.500 inches **Engaging Linkage:** Not included Accommodated Linkage Threaded Hole Thread Size: 1/4-28 **Contact Manual Closing Provision:** Not included **Control Terminal Quantity: Control Terminal Type:** Stud **Grounded Control Terminal:** Included **Main Terminal Quantity: Main Terminal Type:** Stud **Control Terminal Quantity Internally Connected To Main Terminal: Mounting Facility Type And Quantity:**

2 slot

Surface Treatment:

Enamel

Surface Treatment:

Enamel, black

Shelf Life:

N/a

Unit Of Measure:

NSN 2920-00-989-3335

Electrical Engine Starter Relay-solenoid - Page 2 of 2



em			

No

Fiig:

T130-h