

View Online at <https://aerobasegroup.com/nsn/2920-00-989-4260>

Body Material:

Aluminum alloy

Drive Connection Type:

Rigid coupled

Furnished Items:

Ignition coil

Shaft Length:

0.500 inches

Environmental Protection:

Submersible and fungus resistant

Drive Shaft Type:

Plain

Shaft Rotation Direction:

Clockwise

Distributor Cap:

Included

Mounting Method:

Clamp

Impulse Quantity Per Revolution:

6

Ignition Type For Which Designed:

Single

Secondary Terminal Type:

Threaded

Spark Plug Terminal Accommodation Thread Series:

Unef

Primary Terminal Accommodation Type:

Screw

Spark Advance Control Method:

Centrifugal

Maximum Advance Deg:

34.0

Contact Set Quantity:

1

Rpm At Maximum Advance:

2800.0

Primary Terminal Accommodation Thread Series:

Unef

Features Provided:

Radio interference shielding

Spark Distribution Method:

Contact

Spark Plug Terminal Accommodation Thread Diameter:

0.625 inches

Spark Plug Terminal Accommodation Thread Qty Per Inch (tpi):

24

Primary Terminal Accommodation Thread Diameter:

0.750 inches

Primary Terminal Accommodation Thread Qty Per Inch (tpi):

20

Surface Treatment:

Paint

Surface Treatment:

Paint

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A12200