

View Online at <https://aerobasegroup.com/nsn/2920-00-992-0906>

Thread Direction:

Right-hand

Thread Length:

0.563 inches

Second Step Diameter:

0.688 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

0.688 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Keyway Length:

0.625 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Thread Diameter:

0.656 inches

Armature Minimum Speed In Rpm At Full Current Output:

30

Maximum Output Current Rating In Amps:

15.0

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.500 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.500 inches

Angular Deviation Of First Hole From Top Center In Deg:

180.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Distance Between Inside Surfaces Of Hinge Bracket:

6.000 inches

Distance Between Outside Surfaces Of Hinge Bracket:

6.540 inches

Bottom Mounting Hole Diameter:

0.480 inches

Thread Series:

Uns

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

3b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

15.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A14700