

View Online at <https://aerobasegroup.com/nsn/2920-00-992-0906>

**Thread Direction:**

Right-hand

**Thread Length:**

0.563 inches

**Second Step Diameter:**

0.688 inches

**Keyway Width:**

0.156 inches

**Unthreaded Portion Length:**

0.688 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Keyway Length:**

0.625 inches

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Clockwise

**Thread Diameter:**

0.656 inches

**Armature Minimum Speed In Rpm At Full Current Output:**

30

**Maximum Output Current Rating In Amps:**

15.0

**Grounding Method:**

External

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.500 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

3.500 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

180.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

180.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

6.000 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

6.540 inches

**Bottom Mounting Hole Diameter:**

0.480 inches

**Thread Series:**

Uns

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.375 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

16

**Mounting Hole Thread Class:**

3b

**Thready Qty Per Inch (tpi):**

20

**Voltage In Volts:**

15.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700