

View Online at <https://aerobasegroup.com/nsn/2920-01-026-2317>

Thread Direction:

Right-hand

Thread Length:

0.880 inches

Pilot Diameter:

6.540 inches

Second Step Diameter:

0.875 inches

Keyway Width:

0.159 inches

Unthreaded Portion Length:

1.150 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Flange mtd w/two mtg holes, top hole threaded

Pilot Height:

0.750 inches

Keyway Length:

Any acceptable

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

Any acceptable

Thread Diameter:

0.625 inches

Ground Polarity Type:

Negative or positive

Rectifier Location:

Integral

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

4.000 inches

Distance Between Shaft Center And Top Mounting Hole Center:

4.240 inches

Angular Deviation Of First Hole From Top Center In Deg:

180.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Bottom Mounting Hole Diameter:

0.500 inches

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700