

View Online at <https://aerobasegroup.com/nsn/2920-01-030-2001>

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Ground Polarity Type:

Negative

Armature Minimum Speed In Rpm At Full Current Output:

2500

Maximum Output Current Rating In Amps:

60.0

Minimum Current Cut-in Speed In Rpm:

750

Rectifier Location:

Integral

Grounding Method:

Internal

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 3.940 inches and 4.060 inches

Bottom Mounting Hole Diameter:

Between 0.514 inches and 0.524 inches

Maximum Rated Armature Speed In Rpm:

8000

Mounting Hole Thread Series Designator:

Un

Mounting Hole Thread Diameter:

0.500 inches

Mounting Hole Thread Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Voltage In Volts:

14.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700