

View Online at <https://aerobasegroup.com/nsn/2920-01-030-2001>

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Clockwise

**Ground Polarity Type:**

Negative

**Armature Minimum Speed In Rpm At Full Current Output:**

2500

**Maximum Output Current Rating In Amps:**

60.0

**Minimum Current Cut-in Speed In Rpm:**

750

**Rectifier Location:**

Integral

**Grounding Method:**

Internal

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Angular Deviation Of First Hole From Top Center In Deg:**

0.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

Between 3.940 inches and 4.060 inches

**Bottom Mounting Hole Diameter:**

Between 0.514 inches and 0.524 inches

**Maximum Rated Armature Speed In Rpm:**

8000

**Mounting Hole Thread Series Designator:**

Un

**Mounting Hole Thread Diameter:**

0.500 inches

**Mounting Hole Thread Qty Per Inch (tpi):**

16

**Mounting Hole Thread Class:**

2b

**Voltage In Volts:**

14.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A14700