

View Online at <https://aerobasegroup.com/nsn/2920-01-032-5752>

Furnished Items:

Voltage regulator

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Flange mtd w/two mtg holes, top hole threaded

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Ground Polarity Type:

Negative

Armature Minimum Speed In Rpm At Full Current Output:

3000

Minimum Current Cut-in Speed In Rpm:

1000

Rectifier Location:

Integral

Grounding Method:

External

Distance Between Shaft Center And Bottom Mounting Hole Center:

4.000 inches

Distance Between Shaft Center And Top Mounting Hole Center:

4.240 inches

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Bottom Mounting Hole Diameter:

1.000 inches

Maximum Rated Armature Speed In Rpm:

5000

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700