

View Online at <https://aerobasegroup.com/nsn/2920-01-032-5752>

**Furnished Items:**

Voltage regulator

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Flange mtd w/two mtg holes, top hole threaded

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Clockwise

**Ground Polarity Type:**

Negative

**Armature Minimum Speed In Rpm At Full Current Output:**

3000

**Minimum Current Cut-in Speed In Rpm:**

1000

**Rectifier Location:**

Integral

**Grounding Method:**

External

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

4.000 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

4.240 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

0.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

180.0

**Bottom Mounting Hole Diameter:**

1.000 inches

**Maximum Rated Armature Speed In Rpm:**

5000

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.375 inches

**Mounting Hole Thread Qty Per Inch (tpi):**

16

**Mounting Hole Thread Class:**

2b

**Voltage In Volts:**

12.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700