Engine Accessory Generator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-01-103-8052

| Nounting Hole Thread Direction: | |
|--|--------|
| Right-hand | |
| Nounting Style: | |
| lange mtd w/two mtg holes, top hole threaded | |
| Submersibility: | |
| lonsubmersible | |
| Ground Polarity Type: | |
| legative | |
| laximum Output Current Rating In Amps: | |
| 5.0 | |
| Shaft Drive End Style: | |
| Straight shaft end, threaded | |
| Distance Between Shaft Center And Bottom Mounting Hole C | enter: |
| 3.281 inches | |
| Distance Between Shaft Center And Top Mounting Hole Cent | er: |
| 3.235 inches | |
| Angular Deviation Of First Hole From Top Center In Deg: | |
| 0.0 | |
| Angular Deviation Of Second Hole From First Hole In Deg: | |
| 80.0 | |
| Bottom Mounting Hole Diameter: | |
| Between 0.375 inches and 0.385 inches | |
| Iounting Hole Thread Series Designator: | |
| Jnc | |
| Nounting Hole Thread Diameter: | |
| 0.312 inches | |
| Iounting Hole Thready Qty Per Inch (tpi): | |
| 8 | |
| Nounting Hole Thread Class: | |
| b | |
| /oltage In Volts: | |
| 2.0 | |
| Shelf Life: | |
| l/a | |
| Jnit Of Measure: | |
| - | |
| Demilitarization: | |
| lo | |
| iig: | |
| | |