## NSN 2920-01-118-9374

Engine Accessory Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-01-118-9374 **Thread Direction:** Right-hand **Furnished Items:** Fan pulley **Second Step Diameter:** 0.625 inches **Mounting Hole Thread Direction:** Right-hand **Mounting Style:** Flange mtd w/two mtg holes, top hole threaded **Environmental Protection:** Dustproof Submersibility: Nonsubmersible **Shaft Rotation Direction:** Clockwise or counterclockwise **Thread Diameter:** 0.625 inches **Ground Polarity Type:** Negative **Armature Minimum Speed In Rpm At Full Current Output:** 3500 **Maximum Output Current Rating In Amps:** 22.0 Minimum Current Cut-in Speed In Rpm: 1100 **Grounding Method:** External **Shaft Drive End Style:** Straight shaft end, threaded, w/keyway **Distance Between Shaft Center And Bottom Mounting Hole Center:** 3.430 inches **Distance Between Shaft Center And Top Mounting Hole Center:** 3.320 inches **Angular Deviation Of First Hole From Top Center In Deg:** Angular Deviation Of Second Hole From First Hole In Deg: 180.0 **Bottom Mounting Hole Diameter:** 

0.380 inches

**Maximum Rated Armature Speed In Rpm:** 

10000

## NSN 2920-01-118-9374

Engine Accessory Generator - Page 2 of 2



Thread Series:
Unc
Thread Class:
2a
Mounting Hole Thread Series Designator:
Unc
Mounting Hole Thread Diameter:
0.312 inches
Mounting Hole Thready Qty Per Inch (tpi):
18
Mounting Hole Thread Class:
2b
Thready Qty Per Inch (tpi):
18
Voltage In Volts:
12.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A14700