

View Online at <https://aerobasegroup.com/nsn/2920-01-122-1663>

Thread Direction:

Right-hand

Thread Length:

0.480 inches

Pilot Diameter:

5.410 inches

Second Step Diameter:

0.625 inches

Unthreaded Portion Length:

0.620 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Flange mtd w/two mtg holes, top hole threaded

Pilot Height:

0.550 inches

Environmental Protection:

Dustproof

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise or counterclockwise

Thread Diameter:

0.625 inches

Ground Polarity Type:

Negative

Maximum Output Current Rating In Amps:

16.0

Rectifier Location:

Separate

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.430 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.320 inches

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Bottom Mounting Hole Diameter:

0.380 inches

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700