

View Online at <https://aerobasegroup.com/nsn/2920-01-174-5473>

**Thread Direction:**

Right-hand

**Thread Length:**

0.750 inches

**Second Step Diameter:**

Between 0.6684 inches and 0.6990 inches

**Keyway Width:**

0.125 inches

**Unthreaded Portion Length:**

1.312 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Environmental Protection:**

Corrosion resistant and fungus resistant

**Keyway Length:**

0.625 inches

**Submersibility:**

Submersible

**Shaft Rotation Direction:**

Clockwise or counterclockwise

**Distance From End To Keyway Center:**

1.406 inches

**Thread Diameter:**

0.625 inches

**Ground Polarity Type:**

Negative

**Armature Minimum Speed In Rpm At Full Current Output:**

2000

**Maximum Output Current Rating In Amps:**

60.0

**Rectifier Location:**

Integral

**Grounding Method:**

Internal

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

4.187 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

4.187 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

180.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

159.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

Between 7.243 inches and 7.256 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

Between 8.119 inches and 8.132 inches

**Bottom Mounting Hole Diameter:**

0.453 inches

**Maximum Rated Armature Speed In Rpm:**

10000

**Thread Series:**

Unf

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.375 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

16

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

18

**Voltage In Volts:**

28.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700