

View Online at <https://aerobasegroup.com/nsn/2920-01-210-3268>

Thread Length:

0.880 inches

Second Step Diameter:

0.089 inches

Unthreaded Portion Length:

1.150 inches

Mounting Style:

Bracket mtd w/three mtg holes

Unpackaged Unit Length:

9.870 inches

Unpackaged Unit Height:

9.490 inches

Thread Diameter:

0.620 inches

Armature Minimum Speed In Rpm At Full Current Output:

1000

Maximum Output Current Rating In Amps:

100.0

Shaft Drive End Style:

Straight shaft end, threaded

Distance Between Shaft Center And Bottom Mounting Hole Center:

4.090 inches

Distance Between Shaft Center And Top Mounting Hole Center:

4.250 inches

Distance Between Inside Surfaces Of Hinge Bracket:

4.040 inches

Distance Between Outside Surfaces Of Hinge Bracket:

5.100 inches

Top Mounting Hole Diameter:

0.510 inches

Bottom Mounting Hole Diameter:

0.500 inches

Maximum Rated Armature Speed In Rpm:

5000

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

24.0

Fsc Application Data:

Eng elec sys comp, nonaircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700