

View Online at <https://aerobasegroup.com/nsn/2920-01-292-2994>

Thread Direction:

Right-hand

Thread Length:

Between 0.712 inches and 0.732 inches

Second Step Diameter:

Between 0.780 inches and 0.781 inches

Keyway Width:

0.166 inches

Unthreaded Portion Length:

Between 1.248 inches and 1.268 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Keyway Length:

Between 1.000 inches and 1.020 inches

End Application:

2350-01-219-7577

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise or counterclockwise

Distance From End To Keyway Center:

Between 1.336 inches and 1.366 inches

Thread Diameter:

0.750 inches

Maximum Output Current Rating In Amps:

40.0

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

5.200 inches

Distance Between Shaft Center And Top Mounting Hole Center:

5.200 inches

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

10.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 7.200 inches and 7.280 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 8.533 inches and 8.623 inches

Bottom Mounting Hole Diameter:

Between 0.440 inches and 0.462 inches

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

16

Voltage In Volts:

28.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700